

AKW[®]
life. style. choice.

Digital Shower Pumps



A new and enhanced range of quality digital shower pumps ensuring effective and discreet performance

Shower Pumps

Digital shower pumps from AKW are the perfect solution for showering when gravity drainage can't be achieved.

With over 28 years' experience our range is not only easy to install, but also quiet in operation whilst providing reliability and high performance. All digital pumps are compatible with our innovative range of pumped wastes and trays.



Product Codes:

Without waste	25471	25451	25481
With standard 50mm diameter chrome waste	25472	25452	25482
With 90mm diameter chrome waste	25473	25453	25483
With TuffForm pumped waste (PGTF)	25474	-	-
With Screedmaster waste	25475	25455	25485
With Silentflow+ waste (PGTF)	25476	25458	25486

Features:

- + Quick and easy fitting
- + Easily serviceable
- + Efficient debris clearing
- + Virtually silent in operation
- + Pump head uses 4 valves for good debris cleaning
- + Superior performance
- + Good pump accuracy when matched to shower flow
- + Pump head can be rotated to allow flow in either direction
- + Maximum outlet head of 1.0m (39in)
- + Maximum inlet head of 0.5m (19in)
- + Maximum combined head and lift of 1.5m (59in)
- + Supply 230v AC 50Hz 73W
- + IP45 rated and suitable to be installed in Zone 1 or 2 of a shower room
- + Internal TGA fuse
- + Duty cycle 30 mins max on 50% duty
- + Flow meter input

Options:

M11 Digital Shower Pump

For electric showers

- + 11LPM in a 'real life' scenario
- + 15mm inlet & 22mm outlet connectors

M17 Digital Shower Pump

For electric and mixer showers

- + 17LPM in a 'real life' scenario
- + 22mm inlet & outlet connectors

M20 Digital Shower Pump

Ultimate performance for mixer and power showers

- + 20LPM in a 'real life' scenario
- + 22mm inlet & outlet connectors



Pumped Wastes

5yr*
extended warranty
available

IP45



KM507429

SilentFlow+®

The SilentFlow+® pumped waste is a completely new design which is virtually silent in operation to reduce the noise associated with shower pumps and wastes.

- + Noise level testing shows the SilentFlow+® is comparable with the nearest competitors 'quiet' pumped waste at up to 11LPM and outperforms above 11LPM
- + Can be connected to all pumps in the current range
- + Integrated 22mm John Guest fitting

Code: 25414

PW50

50mm standard pumped waste. Issued as standard with both automatic and automatic mixer valve pump kits.

- + Good seals and location
- + Built-in filter
- + Top opening for easy cleaning and rodding
- + 15mm & 22mm John Guest Speedfit outlets available
- + 36mm deep below mounting surface = 15mm
- + 44mm deep below mounting surface = 22mm

Code: 15mm 25122 | 22mm 25405

PW90

90mm diameter pumped waste. Specially designed shallow pump gully (for Mullen® & Sulby 2) with two baffle features that help to reduce the noise during showering cycles.

- + Good seals and location
- + Built-in filter
- + Top opening for easy cleaning and rodding
- + 15mm & 22mm John Guest Speedfit outlets available
- + 36mm deep below mounting surface = 15mm
- + 44mm deep below mounting surface = 22mm

Code: 15mm 25105 | 22mm 25406

PGTF

Tuff-Form pumped gully. Can be specified with any TuffForm® former with vinyl floor covering.

- + Top opening for easy cleaning and rodding
- + 15mm John Guest Speedfit outlet available
- + Depth below tray = 35mm

Code: 25101

SS-PGTF

Stainless Steel Tuff Form pumped gully. Can be specified with any TuffForm® former with tiled floor covering.

- + 22mm outlet pipe
- + Top opening for easy cleaning and rodding
- + Depth below tray = 44mm
- + 22mm John Guest Speedfit outlet
- + Stainless steel plate dimensions 120 x 120mm
- + Plate height is adjustable to a max of 18mm

Code: LB00104

Screedmaster

Screedmaster® pumped gully. For use with graded floor installations with vinyl floor covering.

- + Top opening for easy cleaning and rodding
- + 15mm & 22mm John Guest Speedfit outlet
- + 32mm deep = 15mm outlet
- + 37mm deep = 22mm outlet

Code: 15mm 25100 | 22mm 25407

All pumped waste outlets illustrated are exclusive to AKW.

Guarantee and Certification: EN 60335-1, EN 60335-2-41, EN 62233, EN 61000-3-2, EN 61000-3-3, EN 55014-1, EN 55014-2, EMC Directive 2004/108/EC, Low Voltage Directive 2006/95/EC.

AKW[®]
life. style. choice.

Orders & Quotes

01905 823 299
orders@akw-ltd.co.uk

General Enquiries

01905 823 298
sales@akw-ltd.co.uk

Technical Enquiries

01905 560 219
technicalenquiries@akw-ltd.co.uk

AKW

Pointon Way, Hampton Lovett
Droitwich Spa, WR9 0LR

www.akw-ltd.co.uk
orders.akw-ltd.co.uk



VI 09/16



BS EN ISO 9001:2000 Cert No. 7878
Shower and bathroom equipment