

Product Overview

Latex liquid is designed to be mixed with Bond-it Levelling Compound to give increased flexibility and wearing characteristics.

It is used to improve "water-mix" levelling compounds especially when used on substrates subject to movement i.e. timber. It can also allow levelling compounds to be used as final finish in lightly trafficked areas.



Features & Benefits

- + 1:1 Mix ratio - saving you time, for every 20kg pack of Levelling Compound use 1 container of Latex Liquid.
- + 24 Month shelf life
- + Levelling compound /latex mix sets in 24 hours

Product Specification

+ Mixing

The liquid should be placed in a mixing bucket. Slowly add the powder component to the liquid latex, stirring quickly and continually, until a smooth paste develops. For every 20Kg of Bond It Flooring Compound use 1 container of Bond It Latex Liquid, a mechanical stirrer is recommended for mixing.

+ Application

Porous surfaces should be primed prior to application of levelling compound. Ambient temperature should be between 5°C and 25°C. Do not use in direct sunlight in conservatories. At 25°C the floor should be able to take light traffic in 2-3 hours and floor coverings can be laid after 24 hours.

+ Coverage

1 x 4.5 litre of of Latex liquid per 20kg of Levelling compound.

Up to 3.5m² 1 x 20Kg Levelling compound mixed with 1 x 4.5l Latex liquid

7m² 2 x 20Kg Levelling compound mixed with 2 x 4.5l Latex liquid

+Shelf Life

24 months in unopened containers.

Product Code:

Bond-it Latex Liquid

4.5L

21895

Related Products:

Plywood 4mm	1200mm x 2440mm x 4mm	21884
Plywood 12mm	1200mm x 2440mm x 12mm	21885
CLS Timber Untreated	76mm (3") x 50mm (2") x 2400mm (96")	21886
CLS Timber Treated	76mm (3") x 50mm (2") x 2400mm (96")	21887
AKW Safety flooring (0.5m x 2m): Anthracite	1sqm (2m wide x 0.5m length)	21891-ANT
AKW Safety flooring (0.5m x 2m): Cerulean	1sqm (2m wide x 0.5m length)	21891-CRL
AKW Safety flooring (0.5m x 2m): Dove	1sqm (2m wide x 0.5m length)	21891-DVE
AKW Safety flooring (0.5m x 2m): Rouge	1sqm (2m wide x 0.5m length)	21891-RGE
AKW Safety flooring (0.5m x 2m): Slate	1sqm (2m wide x 0.5m length)	21891-SLT
AKW Safety flooring (0.5m x 2m): Topaz	1sqm (2m wide x 0.5m length)	21891-TPZ
Flooring Weld Rod 1 mtr only : Anthracite	1m	21893-ANT
Flooring Weld Rod 1 mtr only : Cerulean	1m	21893-CRL
Flooring Weld Rod 1 mtr only : Dove	1m	21893-DVE
Flooring Weld Rod 1 mtr only : Rouge	1m	21893-RGE
Flooring Weld Rod 1 mtr only : Slate	1m	21893-SLT
Flooring Weld Rod 1 mtr only : Topaz	1m	21893-TPZ
Vinyl Flooring Coving 3m	3m x 5	30085
Tile to Vinyl Transition Strip	3m x 10	30073
Bond-it Levelling Compound	20kg	21896
Bond-it Contact Adhesive 5L, Toluene-Free	5l	21894